

DASH SIZE	-2	-3	-4	-5	-6	-7	-8	-10	-12	-14	-16	-20	-24	-32
BSP Ø in mm :	1/8" - 28 9,6		1/4" - 19 13,1		3/8" - 19 16,6		1/2" - 14 20,9	5/8" - 14 22,8	3/4" - 14 26,4		1" - 11 33,2	1 1/4" - 11 41,8	1 1/2" - 11 47,7	2" - 11 60
NPT Ø in mm :	1/8" - 27 9,7		1/4" - 18 13,2		3/8" - 18 16,7		1/2" - 14 21		3/4" - 14 26,5		1" - 11½ 33,3	1 1/4" - 11½ 41,8	1 1/2" - 11½ 47,8	2" - 11½ 60,1
JIC (J514) 37° Ø in mm :	5/16" - 24 7,95	3/8" - 24 9,53	7/16" - 20 11,12	1/2" - 20 12,7	9/16" - 18 14,29		3/4" - 16 19,05	7/8" - 14 22,23	1 1/16" - 12 26,99	1 3/16" - 12 30,17	1 5/16" - 12 33,34	1 5/8" - 12 41,28	1 7/8" - 12 47,63	2 1/2" - 12 63,5
SAE (J512) 45° Ø in mm :	5/16" - 24 7,95	3/8" - 24 9,53	7/16" - 20 11,12	1/2" - 20 12,7	5/8" - 18 15,88		3/4" - 16 19,05	7/8" - 14 22,23	1 1/16" - 14 26,99		1 1/4" - 12 31,75	1 3/8" - 12 34,93		
UNF Ø in mm :	5/16" - 24 7,95	3/8" - 24 9,53	7/16" - 20 11,12	1/2" - 20 12,7	9/16" - 18 14,29		3/4" - 16 19,05	7/8" - 14 22,23	1 1/16" - 12 26,99	1 3/16" - 12 30,17	1 5/16" - 12 33,34	1 5/8" - 12 41,28	1 7/8" - 12 47,63	2 1/2" - 12 63,5
ORS (SAE J1453)			9/16" - 18 14,29		11/16" - 16 17,46		13/16" - 16 20,64	1" - 14 25,4	1 3/16" - 12 30,17		1 7/16" - 12 36,51	1 11/16" - 12 42,86	2" - 12 50,8	
JIS 30° (B 0202) (Komatsu)			1/4" - 19 13,1		3/8" - 19 16,6		1/2" - 14 20,9		3/4" - 14 26,4		1" - 11 33,2	1 1/4" - 11 41,8	1 1/2" - 11 47,7	2" - 11 60
PTT 30° Ø in mm :											1 5/16" - 14 33,34	1 5/8" - 14 41,28	1 7/8" - 14 47,63	2 1/2" - 12 63,5
Compression Ø in mm :	5/16" - 24 7,95	3/8" - 24 9,53	7/16" - 24 11,12	1/2" - 24 12,7	9/16" - 24 14,29	5/8" - 24 15,88	11/16" - 20 17,46	13/16" - 18 20,64	1" - 18 25,4		1 1/4" - 18 31,75			
SAE Inverted Flare Ø in mm :	5/16" - 28 7,95	3/8" - 24 9,53	7/16" - 24 11,12	1/2" - 20 12,7	5/8" - 18 15,88	11/16" - 18 17,46	3/4" - 18 19,05	7/8" - 18 22,23	1 1/16" - 16 26,99					
Air Brake Ø in mm :			7/16" - 24 11,12		17/32" - 24 13,49		11/16" - 20 17,46	13/16" - 18 20,64	1" - 18 25,4		1 1/4" - 18 31,75			
BOLT 3000psi (J518/DIN20066)							1/2" 30,2		3/4" 38,1		1" 44,4	1 1/4" 50,8	1 1/2" 60,3	2" 71,4
BOLT 6000psi (J518/DIN20066)							1/2" 31,8		3/4" 41,3		1" 47,6	1 1/4" 54	1 1/2" 63,5	2" 79,4
BOLT Komatsu Ø in mm :							1/2" 30,2	5/8" 34,2	3/4" 38,1		1" 44,5	1 1/4" 50,8	1 1/2" 60,3	2" 71,4

